

CASSETTE AIR-HANDLER



NATURE APPROVES

Customer model			GE1P410I24KRCST	GE1P410I36KRCST	GE1P410I60KRCST
Model			CCA-24CR1	CCA-36CR1	CCA-60CR1
Code			821028300031	821028900039	821030100017
Indoor power supply		V/Ph/Hz	208~230/1/60	208~230/1/60	208~230/1/60
Cooling	Capacity	Btu/h	24000	36000	60000
		W	7032	10548	17580
	Input	W	2420	3840	6290
	Rated current	A	11.1	17.5	29.23
	Input(Indoor unit)	W	150	150	180
	Rated current(Indoor unit)	A	0.7	0.7	0.8
	EER	W/W	2.91	2.75	2.79
Indoor fan motor	Brand		KAIBANG	KAIBANG	KAIBANG
	Model		S.TB-DQ-YDK-45Q-6P2	S.TB-DQ-YDK-45Q-6P2	S.TB-DQ-YDK-75Q-6P2
	Input	W	100	100	180
	Capacitor	μF	2.5	2.5	4
	Speed(Hi/Me/Lo)	r/min	850/730/580	850/730/580	800/750/650
Indoor coil	Number of rows		2	2	2
	Tube pitch(a)xrow pitch(b)	mm	21×13.37	21×13.37	21×13.37
	Fin spacing	mm	1.45	1.45	1.45
	Fin type		Hydrophilic	Hydrophilic	Hydrophilic
	Tube outside dia. and type	mm	Φ7 inner grooved	Φ7 inner grooved	Φ7 inner grooved
	Number of circuits		8	8	12
Indoor air flow(High speed)		m3/h	1200	1200	1900
Indoor noise level		dB(A)	45~52	45~52	51~57
Indoor unit	Dimension(W*D*H)	Body(mm)	840×840×230	840×840×230	840×840×285
		Panel(mm)	950×950×50	950×950×50	950×950×50
	Packing(W*D*H)	Body(mm)	920×920×310	920×920×310	920×920×375
		Panel(mm)	1030×1030×105	1030×1030×105	1030×1030×105
Net/Gross weight	Body(Kg)	28/32	28/32	31/35	
	Panel(Kg)	5.4/8.0	5.4/8.0	5.4/8.0	
Max pressure		MPa	4	4	4.5
Refrigerant type			R410A	R410A	R410A
Refrigerant piping	Liquid side/Gas side	mm	Φ9.52/Φ15.88	Φ9.52/Φ19.05	Φ9.52/Φ19.05
Drainage pipe		mm	25	25	25
Standard controller					
Operation temp		°C	16~32	16~32	16~32
Ambient temp		°C	18~43	18~43	18~43
Application area		m2	28-50	40-70	60~105

Specifications are subject to change without notice ** Model numbers pictures, and specifications of all products are subject to change without further notice.