



NATURE APPROVES

Model			KFRM2410013KR	KFRM2410018KR	KFRM2410024KR	KFRM3610036KR
Power supply		V,HZ,Ph	220-230V,1Ph,60Hz	220-230V,60Hz, 1Ph	220-230V,60Hz, 1Ph	220-230V,60Hz, 1Ph
Cooling	Capacity	Btu/h	12000	18000	24000	36000
	Input	W	1216	1820	2490	3665
	Rated current	A	5.7	8.4	11.4	15.95
	SEER	W/W	13	13	13	13
	Type		Hermetic Motor	ROTARY	ROTARY	ROTARY
	Brand		GMCC	GMCC	GMCC	GMCC
	Capacitor	uF	1.5	1.5	3.0	4.5
	Speed(Hi/Mi/Lo)	r/min	1150/950/800	1180/1000/800	1200/1000/900	1300/1100/990
Indoor noise level (Hi/Mi/Lo)		dB(A)	39/31.5/26.5	42.9/38.2/34.6	47.7/41.3/38.1	48.1/42.5/39.1
Indoor unit	Dimension(W*D*H)	mm	805x194x285	957x213x302	1040x220x327	1146x340x260
	Packing (W*D*H)	mm	870x270x360	1035x295x380	1120x405x310	1265x415x358
	Net/Gross weight	Kg	8.0/10.2	10/12.9	13/16	16/20
Outdoor fan motor	Model		YKT-21-6-10L	YKT-48-6-206	YKT-63-6-200L	YKT-72-6-275L
	Capacitor	uF	1.5	3	3	4.5
Outdoor noise level		dB(A)	53	58.4	57.6	63.2
Outdoor unit	Dimension(W*D*H)	mm	681x285x434	770x300x555	845x363x702	905x375x720
	Packing (W*D*H)	mm	795x345x495	900x348x615	965x395x765	985x405x815
	Net/Gross weight	Kg	23.7/25.6	31.9/34.3	40.8/44	50/55
Refrigerant type		g	R410A/0.46	R410A/560g	R410A/910g	R410A/1650g
	Max. refrigerant pipe length	m	20	25	25	25
	Max. difference in level	m	8	10	10	10
Connection wiring			1.5x3	2.5(Optional)	1.0(Optional)	1.0(Optional)
Plug type			16#x3/SP008弯插	14#x3	--	--
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control
Operation temperature		°C	17~30	17-30	17-30	17-30
Room temperature	Indoor(cooling/ heating)	°C	17~32/	17-32/----	17-32/----	17-32/----
	Outdoor(cooling/heating)	°C	18~43/	18-43/----	18-43/----	18-43/----
Application area (Cooling Standard)		m2	16-23	24-35	32-47	42-60

Specifications are subject to change without notice ** Model numbers pictures, and specifications of all products are subject to change without further notice.

